

## 4" Network IR Middle Speed Dome

## KEY FEATURES

- 4pcs OSRAM IR Array LEDs+2pcs Laser LEDs,IR Distance 100M
- 360° all-frame endless rotation
- Medium Speed PTZ 0.1-40°/S
- ONVIF protocol ,Support most NVR
- SUPPORT P2P, PC/iOS/Android remote control
- Preset cruise, pattern scanning,area scanning, 360°horizontal scanning
- Housing:Aluminum die casting shield
- Waterproof:IP66,Lighting protection:4000V
- Power Supply:DC12V-2A



MP-B401M2-I200 MP-X401M2-I200	MP-B401M2-I500 MP-X401M2-I500
----------------------------------	----------------------------------

- H.265 2.0MP PTZ(Middle Speed)
- 18X Zoom(4.7-84.6mm)(can shows as 30X)

- H.265 5.0MP PTZ(Middle Speed)
- 18X Zoom(4.7-84.6mm)(can shows as 30X)

## 4" Network IR Middle/High Speed Dome

## KEY FEATURES

- 4pcs OSRAM IR Array LEDs+2pcs Laser LEDs,IR Distance 100M
- 360° all-frame endless rotation
- Middle Speed PTZ 0.1-100°/S,High Speed PTZ 0.1-240°/S
- ONVIF protocol ,Support most NVR
- SUPPORT P2P, PC/iOS/Android remote control
- Support POE,Audio
- Preset cruise, pattern scanning,area scanning, 360°horizontal scanning
- Housing:Aluminum die casting shield
- Waterproof:IP66
- Lighting protection:4000V
- Power Supply:DC12V-2A



MP-B401G2PA-I200 MP-X401G2PA-I200	MP-B401G2PA-I500 MP-X401G2PA-I500	MP-B401G2PA-X201S MP-X401G2PA-X201S	MP-B401H2PA-K200T MP-X401H2PA-K200T
--------------------------------------	--------------------------------------	--	--

- H.265 2.0MP Sony PTZ(Middle Speed)
- 18X Zoom(4.7-84.6mm)(can shows as 30X)

- H.265 5.0MP PTZ(Middle Speed)
- 18X Zoom(4.7-84.6mm)(can shows as 30X)

- H.265 2.0MP Sony PTZ(High Speed)
- 20X Zoom(5.4-108mm)+16X Digital Zoom
- Auto-Tracking

## 6" Half Metal Case Network IR Middle Speed Dome

## KEY FEATURES

- 5pcs OSRAM IR Array LEDs+3pcs Laser LEDs,IR Distance 150M
- Medium Speed PTZ 0.05- 40°/S, 360° all-frame endless rotation;
- ONVIF protocol ,Support most NVR
- SUPPORT P2P, PC/iOS/Android remote control
- Preset.cruise, pattern scanning,area scanning, 360°horizontal scanning,255 preset points
- Housing: Aluminum die casting shield
- Waterproof:IP66
- Lighting protection: 4000V
- Power Supply: DC12V-4A



MP-B603M2-Q202S MP-X603M2-Q202S
------------------------------------

- H.265 2.0MP Sony PTZ(Middle Speed)
- 20X Zoom(4.7-94mm)(can shows as 30X)

## 6" Full Metal Case Network IR High Speed Dome

## KEY FEATURES

- 7pcs OSRAM IR Array LEDs+3pcs Laser LEDs, IR Distance 300M
- High Speed PTZ 0.05-240°/S, 360° all-frame endless rotation
- ONVIF protocol ,Support most NVR
- SUPPORT P2P CLOUD ,mobile remote&3D positioning
- Support POE +Audio
- Preset cruise, pattern scanning,area scanning, 360°horizontal scanning,255 preset points;
- Housing:Double shell, Aluminum die casting shield
- Waterproof:IP66
- Lighting protection:6000V
- Power Supply:DC12V-4A
- Optional Functions:  
POE+Audio+Alarm+CVBS+AC24V+DC12V  
RS485+Audio+Alarm+CVBS+DC12V  
RS485+Audio+Alarm+CVBS+AC24V



MP-B601H2PA-X201S MP-X601H2PA-X201S	MP-B601H3PA-D200TS MP-X601H3PA-D200TS
--	--

- H.265 2.0MP Sony Starlight PTZ(High Speed)
- 20X Zoom(4.7-94mm)
- Starlight Low Illumination

- H.265 2.0MP Sony PTZ(High Speed)
- 30X Zoom(4.7-141mm)+4X Digital Zoom
- Starlight Low Illumination,
- Smart Analysis,Non-shaking tracking

## 6" Full Metal Case Network IR High Speed Dome

## KEY FEATURES

- High Speed PTZ 0.05-240°/S, 360° all-frame endless rotation
- ONVIF protocol, Support most NVR
- SUPPORT P2P CLOUD ,mobile remote&3D positioning
- Support POE +Audio
- Preset cruise, pattern scanning,area scanning, 360°horizontal scanning,255 preset points;
- Housing:Double shell, Aluminum die casting shield
- Waterproof:IP66
- Lighting protection:6000V
- Power Supply:DC12V-4A
- Optional Functions:
  - POE+Audio+Alarm+CVBS+AC24V+DC12V
  - RS485+Audio+Alarm+CVBS+DC12V
  - RS485+Audio+Alarm+CVBS+AC24V



MP-B602H2PA-X201S	MP-B601H3PA-D200TS
MP-X602H2PA-X201S	MP-X601H3PA-D200TS

- H.265 2.0MP Sony Starlight PTZ(High Speed)
- 20X Zoom(4.7-94mm)
- Starlight Low Illumination

- H.265 2.0MP Sony PTZ(High Speed)
- 30X Zoom(4.7-141mm)+4X Digital Zoom
- Starlight Low Illumination,
- Smart Analysis,Non-shaking tracking

## 8" Full Metal Case Network IR Speed Dome Camera(Middle/High)

## KEY FEATURES

- 10pcs OSRAM IR Array LEDs,4pcs laser LEDs,IR Distance 300M
- Middle Speed PTZ 0.05-100°/S,High Speed PTZ 0.05-240°/S
- 360° all-frame endless rotation
- ONVIF protocol,Support most NVR
- SUPPORT P2P,mobile remote&3D positioning
- Preset Cruise, pattern scanning,area scanning, 360°horizontal scanning
- Housing:Double shell, Aluminum die casting shield
- Waterproof:IP66
- Lighting protection:8000V
- Power Supply:DC12V-4A
- Optional Functions:
  - POE+Audio+DC12V
  - POE+Audio+Alarm+CVBS+AC24V+DC12V
  - RS485+Audio+Alarm+CVBS+DC12V
  - RS485+Audio+Alarm+CVBS+AC24V



MP-B801G2-Q202S	MP-B801H3-D200TS	MP-B801H35-D240TS
MP-X801G2-Q202S	MP-X801H3-D200TS	MP-X801H35-D240TS

- H.265 2.0MP Sony PTZ(Middle Speed)
- 20X Zoom(4.7-94mm)
- Starlight Illumination

- H.265 2.0MP Sony PTZ(High Speed)
- 30X Zoom(4.7-141mm)+4X Digital Zoom
- Starlight Illumination
- Smart Analysis,Non-shaking tracking

- H.265 2.0MP Sony PTZ(High Speed)
- 35X Zoom(6-210mm)+4X Digital Zoom
- Ultra Colorful day and night

## 8" Full Metal Case Network IR Speed Dome Camera(Middle/High)

## KEY FEATURES

- 8-inch Full Metal High Speed Dome with Full Color
- With the latest Sony Star-Light CMOS sensor,Super WDR for better HLC function,better solved the problem of car headlight effect the image quality of license capture analysis.
- High Speed:0.1-240/S
- With 12pc White Leds,200m IR distance
- Smart Judgment for the brightness exposure requirements of the license plate area,dynamic adjust the power values of LEDs to make the license capture clear by adjust the electronic shutter to the highest value
- Apply to all kinds of low light and no light environment that need to see clear for the car license plate,100-200m scope,the installation height is 3-6 meters,i.e.,Parking lot,illegal capture,illegal U-turns and other low speed monitoring occasions.



MP-B802H3-D200SC
MP-X802H3-D200SC

- H.265 1080P Sony Colorful day and night PTZ
- 30X Zoom(4.7-141mm)+4X Digital Zoom
- Clear capture of license plate at the 100m scope while the car headlight is on

MP-B801H35-D240SC
MP-X801H35-D240SC

- H.265 1080P Sony Ultra colorful day and night PTZ
- 35X Zoom(6-210mm)+4X Digital Zoom,
- Clear capture of license plate at the 200m scope while the car headlight is on



## 4"/6"/8" Infrared Analysis Alert Tracking Network IR High Speed Dome



## KEY FEATURES

- Full Color High Speed Dome
- With the latest Sony Star-Light CMOS sensor, the higher sensitivity and latitude, the perfect image.
- Intrusion detection based on AI intelligent analysis. Supports a variety of behavior detection such as Tripwire, Intrusion, crossing fence, and fast moving. Support multiple trigger rules and linkage actions.
- Support auto tracking function, after finding the target that meets the intrusion rule, the dome will immediately rotate the target-centered position to zoom in and track the target motion. In this way, the monitoring personnel can see clear target characteristics and provide objective and realistic video data for the identity of the suspicious individual and the after-the-fact comparison.
- Support active defense intrusion function: After the target is found, the dome automatically turns to the target position, flashing the visible light, and the audio output line drives the live speaker to send out the voice.

## Intelligent analysis + Active defense + AutoTracking + Star Light illumination



MP-B401G22-Y201SJ MP-X401G22-Y201SJ	MP-B401G25-Y202SJ MP-X401G25-Y202SJ	MP-B604G22-Y201SJ MP-X604G22-Y201SJ	MP-B604G25-Y202SJ MP-X604G25-Y202SJ	MP-B604G30-Y202SJ MP-X604G30-Y202SJ
<ul style="list-style-type: none"> <li>· 4" Middle speed, 2.0 MP Sony</li> <li>· 4PCS Array LEDs+ 2PCS Laser, IR 100M</li> <li>· Rotation speed: 0.5-100°/S</li> <li>· 22X Zoom</li> </ul>	<ul style="list-style-type: none"> <li>· 4" Middle speed, 2.0 MP Sony</li> <li>· 4PCS Array LEDs+ 2PCS Laser, IR 100M</li> <li>· Rotation speed: 0.5-100°/S</li> <li>· 25X Zoom(4.7-117mm), 4X Digital zoom</li> </ul>	<ul style="list-style-type: none"> <li>· 6" Half Metal IR Middle speed dome, 2.0 MP Sony</li> <li>· 7PCS Array LEDs+ 3PCS Laser, IR 300M</li> <li>· 2PCS Alarm flash LEDs</li> <li>· Rotation speed: 0.5-100°/S</li> <li>· 22X Zoom</li> </ul>	<ul style="list-style-type: none"> <li>· 6" Half Metal IR Middle speed dome, 2.0 MP Sony</li> <li>· 7PCS Array LEDs+ 3PCS Laser, IR 300M</li> <li>· 2PCS Alarm flash LEDs</li> <li>· Rotation speed: 0.5-100°/S</li> <li>· 25X Zoom(4.7-117mm), 4X Digital zoom</li> </ul>	<ul style="list-style-type: none"> <li>· 6" Half Metal IR Middle speed dome, 2.0 MP Sony</li> <li>· 7PCS Array LEDs+ 3PCS Laser, IR 300M</li> <li>· 2PCS Alarm flash LEDs</li> <li>· Rotation speed: 0.5-100°/S</li> <li>· 30X Zoom(4.7-141mm), 4X Digital zoom</li> </ul>



MP-B601H22-Y201SJ MP-X601H22-Y201SJ	MP-B601H25-Y201SJ MP-X601H25-Y201SJ	MP-B601H30-Y201SJ MP-X601H30-Y201SJ	MP-A4-F
<ul style="list-style-type: none"> <li>· 6" Full Metal IR High speed dome</li> <li>· 7PCS Array LEDs+ 3PCS Laser, IR 300M</li> <li>· 2PCS Alarm flash LEDs</li> <li>· Rotation speed: 0.5-240°/S</li> <li>· 22X Zoom</li> </ul>	<ul style="list-style-type: none"> <li>· 6" Full Metal IR High speed dome</li> <li>· 7PCS Array LEDs+ 3PCS Laser, IR 300M</li> <li>· 2PCS Alarm flash LEDs</li> <li>· Rotation speed: 0.5-240°/S</li> <li>· 25X Zoom(4.7-117mm), 4X Digital zoom</li> </ul>	<ul style="list-style-type: none"> <li>· 6" Full Metal IR High speed dome</li> <li>· 7PCS Array LEDs+ 3PCS Laser, IR 300M</li> <li>· 2PCS Alarm flash LEDs</li> <li>· Rotation speed: 0.5-240°/S</li> <li>· 30X Zoom(4.7-141mm), 4X Digital zoom</li> </ul>	External waterproof speaker, no need to connect to the power supply, directly connected to the built-in amplifier's PTZ Cameras

## H.265&amp;H.264 NVR Series(Support 1HDD)

## KEY FEATURES

- H.265&H.264 Network Camera Self-adaptive Compatible
- Max support 4K network camera input,ONVIF SPEC 2.6
- Support VGA,HDMI 4K Output
- Multi-Channel synchronous playback
- 2 USB interface,**1CH Face Detection or 2 CH Intrusion Detection**
- 1 SATA interface
- 100M ethernet port
- Third-party cloud storage,Support P2P
- Support mobile message sent,Support GB28181



MP-NVR6104MS

MP-NVR6108MS

MP-NVR6116MS

- 4 Channel Network Digital Video Recorder
- 4ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 4 Channel synchronous playback
- 1 SATA interface,Input/output Broadwidth 48M

- 8 Channel Network Digital Video Recorder
- 8ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 8 Channel synchronous playback
- 1 SATA interface,Input/output Broadwidth 60M

- 16 Channel Network Digital Video Recorder
- 16ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 16 Channel synchronous playback
- 1 SATA interface,Input/output Broadwidth 60M

## H.265&amp;H.264 NVR Series(Support 2HDD)

## KEY FEATURES

- H.265&H.264 Network Camera Self-adaptive Compatible
- Max support 4K network camera input,ONVIF
- Support VGA,HDMI 4K Output
- 2 USB interface
- 2 SATA interface,
- 8ch Alarm input,4ch Alarm output
- 1000M ethernet port
- Third-party cloud storage,Support P2P,
- Support mobile message sent,Support GB28181



MP-NVR6208HS

MP-NVR6216H

MP-NVR6224H

- 8ch H.265&H.264 Network Camera Self-adaptive Compatible
- 1ch Face Detection or Perimeter Intrusion detection optional
- Max 8 Channel synchronous playback
- 2 USB interface,**1CH Face Detection or 2 CH Intrusion Detection**
- 2 SATA interface,Input/output Broadwidth 64M

- 16ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 16 Channel synchronous playback
- 2 SATA interface,Input/output Broadwidth 96M

- 24ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 24 Channel synchronous playback
- 2 SATA interface,Input/output Broadwidth 96M

## H.265&amp;H.264 NVR Series(Support 8HDD)

## KEY FEATURES

- H.265&H.264 Network Camera Self-adaptive Compatible
- Max support 4K network camera input,ONVIF SPEC 2.6
- Support VGA,Dual HDMI port 4K Output
- 2 USB interface
- 8 SATA interface,1 ESATA interface,Input/output Broadwidth 128M
- Max support 6.0MP network camera input,ONVIF
- Dual 1000M ethernet port
- Third-party cloud storage,Support P2P
- Support mobile message sent,Support GB28181



MP-NVR6816HSE

MP-NVR6832HSE

MP-NVR6864HE

- 16ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 16 Channel synchronous playback
- 8 SATA interface,1 ESATA interface,Input/output Broadwidth 128M

- 32ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 32 Channel synchronous playback
- 8 SATA interface,1 ESATA interface,Input/output Broadwidth 128M

- 64ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 64 Channel synchronous playback
- 8 SATA interface,1 ESATA interface,Input/output Broadwidth 128M

## H.265&amp;H.264 NVR Series(Support 16HDD)

## KEY FEATURES

- H.265&H.264 Network Camera Self-adaptive Compatible
- Max support 4K network camera input,ONVIF SPEC 2.6
- Support VGA,Dual HDMI port 4K Output
- 2 USB interface
- 16 SATA interface
- Dual 1000M ethernet port
- Third-party cloud storage,Support P2P,GB 28181
- Support mobile message sent,Support GB28181



MP-NVR61616HE

MP-NVR61632HE

MP-NVR61664HE

MP-NVR616128HE

- 16ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 16 Channel synchronous playback
- 16 SATA interface,1 ESATA interface,Input/output Broadwidth 128M

- 32ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 32 Channel synchronous playback
- 16 SATA interface,1 ESATA interface,Input/output Broadwidth 200M

- 48ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 48 Channel synchronous playback
- 16 SATA interface,1 ESATA interface,Input/output Broadwidth 256M

- 128ch H.265&H.264 Network Camera Self-adaptive Compatible
- Max 128 Channel synchronous playback
- 16 SATA interface,1 ESATA interface,Input/output Broadwidth 384M

## H.265&amp;H.264 POE NVR Series(Support 1HDD)

## KEY FEATURES

- H.265&H.264 Network Camera Self-adaptive Compatible
- Support VGA,HDMI Output
- 2 USB interface
- 100M ethernet port
- Third-party cloud storage,Support P2P
- Support mobile message sent,Support GB28181



MP-NVR2104M-P4	MP-NVR6104MS-P4	MP-NVR6108MS-P4
<ul style="list-style-type: none"> <li>· 4ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· 4ch POE IEEE 802.3af port</li> <li>· Max support 2.0MP network camera input,,ONVIF SPEC 2.6</li> <li>· Max 4 Channel synchronous playback</li> <li>· 1 SATA interface,input/output Broadwidth 32M</li> <li>· HDMI 1080P Output</li> </ul>	<ul style="list-style-type: none"> <li>· 4ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· <b>1ch Face Detection or Perimeter Intrusion detection optional</b></li> <li>· 4ch POE IEEE 802.3af port</li> <li>· Max support 4K network camera input,ONVIF 2.6</li> <li>· Max 4 Channel synchronous playback</li> <li>· 1 SATA interface,input/output Broadwidth 32M</li> <li>· HDMI 4K Output</li> </ul>	<ul style="list-style-type: none"> <li>· 8ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· <b>1ch Face Detection or Perimeter Intrusion detection optional</b></li> <li>· 4ch POE IEEE 802.3af port</li> <li>· Max support 4K network camera input,ONVIF 2.6</li> <li>· Max 8 Channel synchronous playback</li> <li>· 1 SATA interface,input/output Broadwidth 60M</li> <li>· HDMI 4K Output</li> </ul>

MP-NVR6108MS-P8	MP-NVR6116MS-P4
<ul style="list-style-type: none"> <li>· 8ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· <b>1ch Face Detection or 2 ch Perimeter Intrusion detection optional</b></li> <li>· 8ch POE IEEE 802.3af port</li> <li>· Max support 4K network camera input,ONVIF 2.6</li> <li>· Max 8 Channel synchronous playback</li> <li>· 1 SATA interface,input/output Broadwidth 60M</li> <li>· HDMI 4K Output</li> </ul>	<ul style="list-style-type: none"> <li>· 16ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· <b>1ch Face Detection or 2 ch Perimeter Intrusion detection optional</b></li> <li>· 4ch POE IEEE 802.3af port</li> <li>· Max support 4K network camera input,ONVIF 2.6</li> <li>· Max 8 Channel synchronous playback</li> <li>· 1 SATA interface,input/output Broadwidth 60M</li> <li>· HDMI 4K Output</li> </ul>

## H.265&amp;H.264 POE NVR Series(Support 2HDD)

## KEY FEATURES

- 1080P Network Digital Video Recorder
- H.265&H.264 Network Camera Self-adaptive Compatible
- Max support 4K network camera input,ONVIF 2.6
- Support VGA,HDMI 4K Output
- 2 USB interface
- 8ch Alarm input,4ch Alarm output
- 1000M ethernet port
- Third-party cloud storage,Support P2P
- Support mobile message sent,Support GB28181



MP-NVR6208HS-P8	MP-NVR6216H-P8	MP-NVR6216H-P16	MP-NVR6232H-P16
<ul style="list-style-type: none"> <li>· 8ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· 8ch POE IEEE 802.3af port</li> <li>· <b>1ch Local Face Detection or 1ch Perimeter Intrusion detection optional</b></li> <li>· Max 8 Channel synchronous playback</li> <li>· 2 SATA interface ,input/output</li> <li>Broadwidth 64M</li> </ul>	<ul style="list-style-type: none"> <li>· 16ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· 8ch POE IEEE 802.3af port</li> <li>· Max 16 Channel synchronous playback</li> <li>· 2 SATA interface ,input/output</li> <li>Broadwidth 96M</li> </ul>	<ul style="list-style-type: none"> <li>· 16ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· 16ch POE IEEE 802.3af port</li> <li>· Max 16 Channel synchronous playback</li> <li>· 2 SATA interface ,input/output</li> <li>Broadwidth 128M</li> </ul>	<ul style="list-style-type: none"> <li>· 32ch H.265&amp;H.264 Network Camera Self-adaptive Compatible</li> <li>· 16ch POE IEEE 802.3af port</li> <li>· Max 16 Channel synchronous playback</li> <li>· 2 SATA interface ,input/output</li> <li>Broadwidth 256M</li> </ul>



## 4K Analogue Camera

### KEY FEATURES

- HD 4K Plastic Indoor Dome Camera
- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night
- OSD menu, DNR, Smart IR,ICR
- IR range: 20~25m
- Wide Voltage,UTC
- Surge protection
- DC12V



- HD 4K Plastic Indoor Dome Camera
- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night
- OSD menu, DNR, Smart IR,ICR,UTC
- IR range: 30~40m
- Wide Voltage
- Surge protection
- DC12V



**MP-Q1VH801F-O**

- HD 8.0MP 1/1.9" high-performance CMOS
- True WDR
- 4.5mm Lens/8.0MP



**MP-Q1VH800F-A**

- HD 8.0MP 1/2.3" high-performance CMOS
- 4.5mm Lens/8.0MP
- DWDR

**MP-Q9VH800V-A**

- HD 8.0MP 1/2.3" high-performance CMOS
- Varifocal 3.6-10mm Lens/8.0MP
- DWDR

### KEY FEATURES

- HD 4K Metal Indoor Dome Camera
- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night
- OSD menu, DNR, Smart IR,ICR
- IR range: 30~40m
- Wide Voltage,UTC
- Surge protection
- DC12V,IP67



### KEY FEATURES

- HD 4K Metal Indoor Dome Camera
- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night
- OSD menu, DNR, Smart IR,ICR,UTC
- IR range: 30~40m
- Wide Voltage
- Surge protection
- DC12V,IP66



**MP-F5AH801V-O**

- HD 8.0MP 1/1.9" high-performance CMOS
- True WDR
- Varifocal 3.6-10mm Lens/8.0MP



**MP-F5AH800V-A**

- HD 8.0MP 1/2.3" high-performance CMOS
- Varifocal 3.6-10mm Lens/8.0MP
- DWDR

**MP-M9AH800V-A**

- HD 8.0MP 1/2.3" high-performance CMOS
- Varifocal 3.6-10mm Lens/8.0MP
- DWDR

### KEY FEATURES

- HD 4K Metal Outdoor Bullet Camera
- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night
- OSD menu, DNR, Smart IR,ICR
- IR range: 35~45m
- Wide Voltage,UTC
- Surge protection
- DC12V,IP67



### KEY FEATURES

- HD 4K Metal Outdoor Bullet Camera
- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night
- OSD menu, DNR, Smart IR,ICR
- IR range: 35~45m
- Wide Voltage,UTC
- Surge protection
- DC12V,IP67



**MP-L8QH801V-O**

- HD 8.0MP 1/1.9" high-performance CMOS
- True WDR
- Varifocal 3.6-10mm Lens/8.0MP



**MP-L8QH800V-A**

- HD 8.0MP 1/2.3" high-performance CMOS
- Varifocal 3.6-10mm Lens/8.0MP
- DWDR

**MP-L9GH801V-O**

- HD 8.0MP 1/1.9" high-performance CMOS
- True WDR
- Varifocal 3.6-10mm Lens/8.0MP



**MP-L9GH800V-A**

- HD 8.0MP 1/2.3" high-performance CMOS
- Varifocal 3.6-10mm Lens/8.0MP
- DWDR

**MP-L8QH801M-O**

**MP-L8AH801M-O**

**MP-L8GH801M-O**

**MP-L8JH801M-O**

- HD 4K Metal Outdoor Bullet Camera**
- 1/1.9" high-performance CMOS
  - AHD/CVI/TVI/CVBS output OSD switchable
  - True Day/Night Color: 0.01Lux @F1.2, B/W: 0.001Lux with IR on, True WDR
  - 3.6-11mm Motorized Lens/8.0MP
  - OSD menu, DNR, Smart IR,ICR
  - IR range: 40~60m
  - Wide Voltage,UTC
  - Surge protection
  - DC12V,IP67

# 4K UHD ANALOGUE SERIES

## Temperature and Humidity Camera with Alarm

**KEY FEATURES**

- HD 2.4MP Metal Outdoor Bullet Camera  
 · 1/3" Sony+Eyenix high-performance CMOS  
 · AHD/CVI/TVI/CVBS 1080P output  
 · True Day/Night,Ultra Low illumination  
 · OSD menu, UTC support,  
 · 3D DNR, Sense Up  
 · Smart IR,up to 20M IR distance  
 · Auto focus 2.8-12mm lens  
 · Wide Voltage,Super WDR  
 · Surge protection  
 · DC12V,Defog,HLC  
 · With Alarm Function,1pc Alarm



MP-L8BH241M4-BTHA3

**KEY FEATURES**

- HD 2.4MP Metal Indoor Dome Camera  
 · 1/3" Sony+Eyenix high-performance CMOS  
 · AHD/CVI/TVI/CVBS 1080P output  
 · True Day/Night,Ultra Low illumination  
 · OSD menu, UTC support  
 · 3D DNR, Sense Up  
 · Smart IR,up to 40M IR distance  
 · Wide Voltage,Super WDR  
 · Surge protection  
 · DC12V,Defog,HLC



MP-L8BH241M4-BTH

- HD 2.4MP temperature and humidity camera
- Auto focus 2.8-12mm lens

MP-L9BH241V4-BTH

- HD 2.4MP temperature and humidity camera
- Manual 2.8-12mm varifocal lens

**Temperature and Humidity Detection****Super WDR****4X Optical Zoom****HLC(License plate camera)****Defog function**



## Ultra Colorful Day and Night Camera

### KEY FEATURES

Ultra 2.4MP HD 2 in 1 Full Color Day&Night Dome Camera

- 1/1.9"Progressive CMOS SONY
- ICR, 0.0001LUX without IR
- 2 IN 1(AHD/TVI) Output
- 1920x1080:25fps(P)/30fps(N)
- 5.5mm lens(3.6mm)/3.0MP
- DWDR, 3D DNR, BLC
- Low illumination
- 6KV,DC12V



MP-Q1VSH240F-O

### KEY FEATURES

Ultra 2.4MP HD 2 in 1 Full Color Day&Night Metal Dome Camera

- 1/1.9"Progressive CMOS SONY
- ICR, 0.0001LUX without IR
- 2 IN 1(AHD/TVI) Output
- 1920x1080:25fps(P)/30fps(N)
- 5.5mm lens(3.6mm)/3.0MP
- DWDR, 3D DNR, BLC
- Low illumination
- 6KV,DC12V,IP67



MP-F5BSH240F-O

### KEY FEATURES

Ultra 2.4MP HD 2 in1 Full Color Day&Night Metal Bullet Camera

- 1/1.9"Progressive CMOS SONY
- ICR, 0.0001LUX without IR
- 2 IN 1(AHD/TVI) Output
- 1920x1080:25fps(P)/30fps(N)
- 5.5mm lens(3.6mm)/3.0MP
- DWDR, 3D DNR, BLC
- Low illumination
- 6KV,DC12V,IP67



MP-L1QSH240F-O

### KEY FEATURES

2.0MP HD 2 in 1 Starlight Bullet Camera

- 1/1.9"Progressive CMOS SONY
- ICR, 0.0001LUX without IR
- 2 IN 1(AHD/TVI) Output
- 1920x1080:25fps(P)/30fps(N)
- Varifocal Lens:3.6-11mm/3.0MP
- DWDR, 3D DNR, BLC
- Low illumination
- 6KV,DC12V,IP67



MP-L8QSH240V-O

### Traditional IR Camera At Night



### Ultra Day&Night Colorful Camera



### Day&Night Colorful Camera



### Ultra Day&Night Colorful Camera



## Star Light 4-IN-1 Camera

### KEY FEATURES

- HD Starlight Dome Camera
- 4 IN 1(AHD/CVI/TVI/CVBS) Output
- 3D DNR, BLC
- IR range: 20~25m
- 6KV,DC12V



MP-Q1VSH210F-O	MP-Q1VSH201F-O	MP-Q1VSH200F-O	MP-F5BSH210F-O	MP-F5BSH201F-O	MP-F5BSH200F-O
<ul style="list-style-type: none"> <li>· 2.1MP 1/2.7"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· True WDR</li> </ul> <span style="background-color: red; color: white; padding: 2px 5px; border-radius: 10px;">WDR</span>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.1MP 1/2.7"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· True WDR</li> </ul> <span style="background-color: red; color: white; padding: 2px 5px; border-radius: 10px;">WDR</span>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>

### KEY FEATURES

- HD Starlight Bullet Camera
- 4 IN 1(AHD/CVI/TVI/CVBS) Output
- 3D DNR, BLC
- IR range: 30~35m
- Low illumination
- 6KV,DC12V,IP66



MP-L2QSH210F-O	MP-L2QSH201F-O	MP-L2QSH200F-O
<ul style="list-style-type: none"> <li>· 2.1MP 1/2.7"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· True WDR</li> </ul> <span style="background-color: red; color: white; padding: 2px 5px; border-radius: 10px;">WDR</span>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>

### KEY FEATURES

- HD Starlight Bullet Camera
- 4 IN 1(AHD/CVI/TVI/CVBS) Output
- 3D DNR, BLC
- IR range: 30~35m
- Low illumination
- 6KV,DC12V,IP66



MP-L1QSH210F-O	MP-L1QSH201F-O	MP-L1QSH200F-O
<ul style="list-style-type: none"> <li>· 2.1MP 1/2.7"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· True WDR</li> </ul> <span style="background-color: red; color: white; padding: 2px 5px; border-radius: 10px;">WDR</span>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· 3.6mm lens/3.0MP</li> <li>· DWDR</li> </ul>

### KEY FEATURES

- HD Starlight Bullet Camera
- 4 IN 1(AHD/CVI/TVI/CVBS) Output
- 3D DNR, BLC
- IR range: 35~45m
- Low illumination
- 6KV,DC12V,IP67



MP-L8QSH210V-O	MP-L8QSH201V-O	MP-L8QSH200V-O
<ul style="list-style-type: none"> <li>· 2.1MP 1/2.7"Progressive CMOS SONY</li> <li>· Varifocal Lens:2.8-12mm/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· Varifocal Lens:2.8-12mm/3.0MP</li> <li>· True WDR</li> </ul> <span style="background-color: red; color: white; padding: 2px 5px; border-radius: 10px;">WDR</span>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· Varifocal Lens:2.8-12mm/3.0MP</li> <li>· DWDR</li> </ul>

### KEY FEATURES

- HD Starlight Bullet Camera
- 4 IN 1(AHD/CVI/TVI/CVBS) Output
- 3D DNR, BLC
- IR range: 35~45m
- Low illumination
- 6KV,DC12V,IP67



MP-L8ASH210M-O	MP-L8ASH201M-O	MP-L8ASH200M-O
<ul style="list-style-type: none"> <li>· 2.1MP 1/2.7"Progressive CMOS SONY</li> <li>· Auto Focus Lens:2.8-12mm/3.0MP</li> <li>· DWDR</li> </ul>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· Auto Focus Lens:2.8-12mm/3.0MP</li> <li>· True WDR</li> </ul> <span style="background-color: red; color: white; padding: 2px 5px; border-radius: 10px;">WDR</span>	<ul style="list-style-type: none"> <li>· 2.0MP 1/2.8"Progressive CMOS SONY</li> <li>· Auto Focus Lens:2.8-12mm/3.0MP</li> <li>· DWDR</li> </ul>

## Plastic Indoor Dome Camera

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night, IR range: 20~25m
- OSD menu, DNR, Smart IR, ICR, UTC Optional
- Wide Voltage, DWDR
- Surge protection
- DC12V



MP-Q1VH501F-A	MP-Q1VH503F-A	MP-Q1VH401F-A	MP-Q1VH202F-A	MP-Q1VH100F-A	MP-Q1VH200F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night, IR range: 30~40m
- OSD menu, DNR, Smart IR, ICR, UTC Optional
- Wide Voltage, DWDR
- Surge protection
- DC12V



MP-Q9VH501V-A	MP-Q9VH503V-A	MP-Q9VH401V-A	MP-Q9VH202V-A	MP-Q9VH200V-A	MP-Q9VH100V-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night, IR range: 20~25m
- OSD menu, DNR, Smart IR, ICR, UTC Optional optional
- Wide Voltage, DWDR.
- DC12V, Surge protection



MP-Q2EH501F-A	MP-Q2EH503F-A	MP-Q2EH401F-A	MP-Q2EH202F-A	MP-Q2EH200F-A	MP-Q2EH100F-A
. HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	. HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	. HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	. HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

## Metal Indoor Dome Camera

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 20~25m
- OSD menu, DNR, Smart IR, ICR, UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP66



MP-M1AH501F-A	MP-M1AH503F-A	MP-M1AH401F-A	MP-M1AH202F-A	MP-M1AH200F-A	MP-M1AH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30~40m
- OSD menu, DNR, Smart IR, ICR, UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP66



MP-M9AH501V-A	MP-M9AH503V-A	MP-M9AH401V-A	MP-M9AH202V-A	MP-M9AH200V-A	MP-M9AH100V-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/2.0MP

## Metal Indoor Dome Camera

### KEY FEATURES

Metal Indoor Dome Camera

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 25~30m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP66



MP-M1UH501F-A	MP-M1UH503F-A	MP-M1UH401F-A	MP-M1UH202F-A	MP-M1UH200F-A	MP-M1UH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- 1/2.5" high-performance CMOS
- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 20~25m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-F1DH501F-A	MP-F1DH503F-A	MP-F1DH401F-A	MP-F1DH202F-A	MP-F1DH200F-A	MP-F1DH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night, IR range: 20~25m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-F5BH501F-A	MP-F5BH503F-A	MP-F5BH401F-A	MP-F5BH202F-A	MP-F5BH200F-A	MP-F5BH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30~40m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-F5AH501V-A	MP-F5AH503V-A	MP-F5AH401V-A	MP-F5AH202V-A	MP-F5AH200V-A	MP-F5AH100V-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night, IR range: 30~40m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67,Junction box



MP-F5CH501V-A	MP-F5CH503V-A	MP-F5CH401V-A	MP-F5CH202V-A	MP-F5CH200V-A	MP-F5CH100V-A
4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/2.0MP

## Metal Fisheye Indoor Dome Camera

### KEY FEATURES

Metal Fisheye Indoor Dome Camera

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 20 ~ 25m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V



MP-T1FH501F-A	MP-T1FH503F-A	MP-T1FH401F-A	MP-T1FH202F-A	MP-T1FH200F-A	MP-T1FH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 1.44mm Lens	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 1.44mm Lens	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 1.44mm Lens	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 1.44mm Lens	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 1.44mm Lens	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 1.44mm Lens

## Plastic Outdoor Bullet Camera

### KEY FEATURES

- 1/2.5" high-performance CMOS
- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 25 ~ 30m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP66



MP-P1AH501F-A	MP-P1AH503F-A	MP-P1AH401F-A	MP-P1AH202F-A	MP-P1AH200F-A	MP-P1AH100F-A
HD 5.1MP Plastic Outdoor Bullet Camera · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP Plastic Outdoor Bullet Camera · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP Plastic Outdoor Dome Camera · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP Plastic Outdoor Dome Camera · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP Plastic Outdoor Dome Camera · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP Plastic Outdoor Dome Camera · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

## Metal Outdoor Bullet Camera

### KEY FEATURES

- Metal Outdoor Bullet Camera
- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30 ~ 35m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L1UH501F-A	MP-L1UH503F-A	MP-L1UH401F-A	MP-L1UH202F-A	MP-L1UH200F-A	MP-L1UH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30 ~ 35m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L4AH501F-A	MP-L4AH503F-A	MP-L4AH401F-A	MP-L4AH202F-A	MP-L4AH200F-A	MP-L4AH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30 ~ 35m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L2QH501F-A	MP-L2QH503F-A	MP-L2QH401F-A	MP-L2QH202F-A	MP-L2QH200F-A	MP-L2QH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

## Metal Outdoor Bullet Camera

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30 ~ 35m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L2JH501F-A	MP-L2JH503F-A	MP-L2JH401F-A	MP-L2JH202F-A	MP-L2JH200F-A	MP-L2JH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30 ~ 35m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L1QH501F-A	MP-L1QH503F-A	MP-L1QH401F-A	MP-L1QH202F-A	MP-L1QH200F-A	MP-L1QH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 30 ~ 35m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L8NH501F-A	MP-L8NH503F-A	MP-L8NH401F-A	MP-L8NH202F-A	MP-L8NH200F-A	MP-L8NH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

**KEY FEATURES**

- Metal Outdoor Bullet Camera
- AHD/CVI/TVI/CVBS output one-button switching
  - True Day/Night,IR range: 30 ~ 35m
  - OSD menu, DNR, Smart IR,ICR,UTC Optional
  - Wide Voltage,DWDR
  - Surge protection
  - DC12V,IP67



MP-L8UH501F-A	MP-L8UH503F-A	MP-L8UH401F-A	MP-L8UH202F-A	MP-L8UH200F-A	MP-L8UH100F-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · 3.6mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 3.6mm Lens/3.0MP	HD 2.0MP 4-IN-1 · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

**KEY FEATURES**

- Metal Outdoor Bullet Camera
- AHD/CVI/TVI/CVBS output one-button switching
  - True Day/Night,IR range: 35 ~ 45m
  - OSD menu, DNR, Smart IR,ICR,UTC Optional
  - Wide Voltage,DWDR
  - Surge protection
  - DC12V,IP67



MP-L9UH501V-A	MP-L9UH503V-A	MP-L9UH401V-A	MP-L9UH202V-A	MP-L9UH100V-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP

## Metal Outdoor Bullet Camera

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 35~45m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L8QH501V-A	MP-L8QH503V-A	MP-L8QH401V-A	MP-L8QH202V-A	MP-L8QH100V-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output one-button switching
- True Day/Night,IR range: 35~45m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67,Junction box



MP-L9GH501V-A	MP-L9GH503V-A	MP-L9GH401V-A	MP-L9GH202V-A	MP-L9GH100V-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · Varifocal 2.7-12mm Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.7-12mm Lens/5.0MP	HD 4.0MP 4-IN-1 · 1/3" high-performance CMOS · Varifocal 2.8-12mm Lens/4.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · Varifocal 2.8-12mm Lens/3.0MP	HD 1.0MP 4-IN-1 · 1/4" high-performance CMOS · Varifocal 2.8-12mm Lens/3.0MP

## Auto- Focus Dome Series

### KEY FEATURES

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 30~40m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP66



MP-M2AH504M-O	MP-M2AH503M	MP-M2AH202M-A
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 30~40m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP67



MP-F5AH504M-O	MP-F5AH503M-O	MP-F5AH202M-B
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP

### KEY FEATURES

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 30~40m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP67



MP-F5CH504M-O	MP-F5CH503M-O	MP-F5CH202M-B
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP

## Auto-Focus Bullet Series

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 35~45m
- OSD menu, DNR, Smart IR,ICR
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP67



MP-L8AH504M-O	MP-L8AH503M-O	MP-L8AH202M-B
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 35~45m
- OSD menu, DNR, Smart IR,ICR,UTC Optional
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP67



MP-L8QH504M-O	MP-L8QH503M-O	MP-L8QH202M-B
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 35~45m
- OSD menu, DNR, Smart IR,ICR
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP67



MP-L8GH504M-O	MP-L8GH503M-O	MP-L8GH202M-B
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP

**KEY FEATURES**

- AHD/CVI/TVI/CVBS output OSD switchable
- True Day/Night,IR range: 40~50m
- OSD menu, DNR, Smart IR,ICR
- Wide Voltage,DWDR,UTC Optional
- Surge protection
- DC12V,IP67



MP-L8JH504M-O	MP-L8JH503M-O	MP-L8JH202M-B
HD 5.1MP 4-IN-1 · 1/2.5" high-performance CMOS · 2.8-12mm Motorized Lens/5.0MP	HD 5.0MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/5.0MP	HD 2.1MP 4-IN-1 · 1/2.9" high-performance CMOS SONY · 2.8-12mm Motorized Lens/3.0MP



**Mapesen,Your Reliable Partner !**

# HD ANALOGUE SERIES - 4-IN-1 Camera ENTRY Series

## Plastic Indoor Dome Camera

### KEY FEATURES

- True Day/Night,IR range: 20~25m
- OSD menu, DNR, Smart IR,ICR,UTC
- Wide Voltage,DWDR
- Surge protection
- DC12V



MP-Q1WH500F-A	MP-Q1WH400F-A	MP-Q1WH203F-A	MP-Q1WA206F	MP-Q1WA101F
HD 5MP 4-IN-1 one-button switching · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 4MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/5.0MP	HD 2.1MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 2.0MP · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 1.0MP · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

### KEY FEATURES

- True Day/Night,IR range: 20~25m
- OSD menu, DNR, Smart IR,ICR,UTC
- Wide Voltage,DWDR
- Surge protection
- DC12V



MP-Q3RH500F-A	MP-Q3RH400F-A	MP-Q3RH203F-A	MP-Q3RA206F	MP-Q3RA101F
HD 5MP 4-IN-1 one-button switching · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 4MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/5.0MP	HD 2.1MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 2.0MP · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 1.0MP · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

## Metal Indoor Dome Camera

### KEY FEATURES

- True Day/Night,IR range: 20~25m
- OSD menu, DNR, Smart IR,ICR,UTC
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP66



MP-M1AH500F-A	MP-M1AH400F-A	MP-M1AH203F-A	MP-M1AA206F	MP-M1AA101F
HD 5MP 4-IN-1 one-button switching · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 4MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/5.0MP	HD 2.1MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 2.0MP · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 1.0MP · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP

## Plastic Outdoor Bullet Camera

### KEY FEATURES

- True Day/Night,IR range: 25~30m
- OSD menu, DNR, Smart IR,ICR,UTC
- Wide Voltage,DWDR
- Surge protection
- DC12V



MP-P1AH500F-A	MP-P1AH400F-A	MP-P1AH203F-A	MP-P1AA206F	MP-P1AA101F
HD 5MP 4-IN-1 one-button switching · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 4MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/5.0MP	HD 2.1MP 4-IN-1 one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 2.0MP · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 1.0MP · 3.6mm Lens/2.0MP

## Metal Outdoor Bullet Camera

### KEY FEATURES

- True Day/Night,IR range: 25~30m
- OSD menu, DNR, Smart IR,ICR,UTC
- Wide Voltage,DWDR
- Surge protection
- DC12V,IP67



MP-L2UH500F-A	MP-L2UH400F-A	MP-L2UH203F-A	MP-L2UA206F	MP-L2UA101F
HD 5MP one-button switching · 1/2.5" high-performance CMOS · 4mm Lens/5.0MP	HD 4MP one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/5.0MP	HD 2.1MP one-button switching · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 2.0MP · 1/2.7" high-performance CMOS · 3.6mm Lens/3.0MP	AHD 1.0MP · 1/4" high-performance CMOS · 3.6mm Lens/2.0MP